

ESPECIFICACIONES TÉCNICAS PARA PLANTAS ELÉCTRICAS GP

CUMMINS

CUMMINS					VOLTAJE DE GENERADOR 220V						VOLTAJE DE GENERADOR 440V / 480V			
CAPACIDAD	MOTOR	GENERADOR	DEPPSEA	COMAP	220V	INT GEN	Transferencia / CNC Electric		TABLERO TRANSFE	440V	INT GEN	Transferencia / CNC Electric		TABLERO TRANSFE
GP-20	X2.5G4	S0L2-M1	4520	AMF08	65.69	60 A	70 A	DOBLE TIRO	A	32.81		ESP	DOBLE TIRO	A
GP-30	X3.3G2	S1L2-J1	4520	AMF08	98.53	100 A	100 A	DOBLE TIRO		49.21		60 A	DOBLE TIRO	
GP-40	4BTAA3.3G18	UCI224D	4520	AMF08	131.37	125 A	120 A	DOBLE TIRO		65.61	60 A	70 A	DOBLE TIRO	
GP-50	4BTAA3.3G17	UCI224D	4520	AMF08	164.21	160 A	160 A	DOBLE TIRO		82.01	100 A	100 A	DOBLE TIRO	
GP-60	4BTAA3.3G12	S1L2-Y1	4520	AMF08	197.06	200 A	200 A	DOBLE TIRO		98.42	100 A	100 A	DOBLE TIRO	
GP-80	6BTA5.9G6	UCI224G	4520	AMF08	262.74	250 A	275 A	DOBLE TIRO	B	131.22	160 A	160 A	DOBLE TIRO	A
GP-100	6BTA5.9G6	UCI274C	4520	AMF08	328.43	400 A	350 A	DOBLE TIRO		164.03	160 A	160 A	DOBLE TIRO	
GP-125	6BTA5.9G6	UCI274E	4520	AMF08	410.54	400 A	400 A	DOBLE TIRO		205.03	200 A	200 A	DOBLE TIRO	
GP-150	6CTAA8.3-G7	UCI274F	4520	AMF08	492.64	630 A	500 A	DOBLE TIRO		246.04	250 A	275 A	DOBLE TIRO	
GP-175	6CTAA8.3G7	UCI274H	4520	AMF08	574.75	630 A	630 A	DOBLE TIRO		287.05	250 A	275 A	DOBLE TIRO	
GP-200	6CTAA8.3-G7	UCI274H	4520	AMF08	656.86	630 A	630 A	DOBLE TIRO	C	328.05	400 A	350 A	DOBLE TIRO	B
GP-250	QSL9-G3	UCDI274K	7420	AMF20	821.07	800 A	800 A	DOBLE TIRO		410.06	400 A	400 A	DOBLE TIRO	
GP-300	QSL9.G5	S4L1D.D4	7420	AMF20	985.29	1000 A	1000 A	DOBLE TIRO		492.08	630 A	500 A	DOBLE TIRO	
GP-350	QSG12-G3	S4L1D-E4	7420	AMF20	1149.50	1250 A	1250 A	DOBLE TIRO		574.09	630 A	630 A	DOBLE TIRO	
GP-400	QSZ13-G5	S4L1D-F4	7420	AMF20	1313.72	1250 A	1250 A	DOBLE TIRO		659.10	630 A	630 A	DOBLE TIRO	
GP-500	QSX15.G9	HCI534D	7420	AMF20	1642.14	1600 A	1600 A	DOBLE TIRO	D	820.13	800 A	800 A	DOBLE TIRO	C
GP-600	VTA28-G5	HCI534E	7420	AMF20	1970.57	2000 A	2000 A	DOBLE TIRO		984.16	1000 A	1000 A	DOBLE TIRO	
GP-800	QSK23-G3	S6L1D-C4	7420	AMF20	2627.43	2500 A	2500 A	DOBLE TIRO		1312.21	1250 A	1250 A	DOBLE TIRO	
GP-1000	KTA38-G4	S6L1D-E4	7420	AMF20	3284.29	3200 A	3200 A	ELECTROS		1640.26	1600 A	1600 A	DOBLE TIRO	
GP-1250	KTA50-G3	S6L1D-H4	7420	AMF20						2050.32	2000 A	2000 A	DOBLE TIRO	
GP-1500	KTA50-G9	PI734C	7420	AMF20					E	2460.39	2500 A	2500 A	DOBLE TIRO	D
GP-2000	QSK60.G6	PI734F	7420	AMF20						3280.52	3200 S	3200 A	ELECTROS	

DIMENSIONES Y PESO DE TABLEROS DE TRANSFERENCIA GP

A 30 - 275 A
ALTO - 82 cm
FRENTE - 56 cm
FONDO - 30 cm

80 Kg

B 350 - 630 A
ALTO - 1.48 cm
FRENTE - 70 cm
FONDO - 60 cm

120 Kg

C 800 - 1250 A
ALTO - 1.86 mts
FRENTE - 90 cm
FONDO - 82.5 cm

200 Kg

D 1600 - 2500 A
ALTO - 2.10 mts
FRENTE - 90 cm
FONDO - 1.22 mts

250 Kg

E* 1600 - 6300 A
ALTO - 2.28 mts
FRENTE - 90 cm
FONDO - 92 mts

290 Kg

*Tablero Especial
Con interruptores eléctricos